

Yealink

T34W



KEY FEATURES

- 2.4" 320 x 240 Color LCD Display
- Built-in Dual Band 2.4G/5G Wi-Fi
- USB 2.0 Port For Wired USB Headsets
- Dual-port Gigabit Ethernet
- PoE Support

GIGABIT, WI-FI ENABLED IP PHONE WITH FOUR LINES

The **Yealink T34W** is an entry-level IP phone offering seamless connectivity and a quality visual experience. Equipped with an extra-large color screen, dual-band 5G Wi-Fi, and support for up to 4 lines, the T34W is perfect for small and large office environments alike.

YEALINK T34W SPECIFICATIONS

Audio Features

- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Wideband codec: G.722
- Narrowband codec: PCMU (G.711A), PCMA(G.711μ), G.729
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 4 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser, action URL/URI

- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Built-in dual-band Wi-Fi:
 - Network standard: IEEE802.11a/b/g/n/ac
 - Transmission rate: Up to 433Mbps (dynamic)
 - Frequency range: 2.4GHz/5.0GHz
- USB port (2.0 compliant) for: Yealink wired Bluetooth headsets
- Enhanced DSS Key

YEALINK T34W



Directory

- › Local phonebook up to 1000 entries
- › Blacklist
- › XML/LDAP remote phonebook
- › Smart dialing
- › Phonebook search/import/export
- › Call history: dialed/received/missed/forwarded

IP-PBX Features

- › Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- › Anonymous call, anonymous call rejection
- › Hot-desking, voice mail
- › Flexible seating
- › Call park, call pickup
- › Executive and Assistant
- › Centralized call recording
- › Visual voice mail
- › Call recording

Display and Indicator

- › 2.3" 320 x 240-pixel graphical LCD with backlight
- › 16-bit depth color
- › LED for call and message waiting indication
- › Dual-color (red or green) illuminated LEDs for line status information
- › Wallpaper
- › Intuitive user interface with icons and soft keys
- › Multilingual user interface
- › Caller ID with name and number
- › Screensaver
- › Power saving

Feature keys

- › 4 line keys with LED
- › 4 line keys can be programmed up to 12 paperless DSS keys (4-page view)
- › 5 feature keys: transfer, message, headset, redial, mute, hands-free speakerphone
- › 6 navigation keys
- › Volume control keys

Interface

- › Dual-port Gigabit Ethernet
- › Power over Ethernet (IEEE 802.3af), class 2
- › 1 x RJ9 (4P4C) handset port
- › 1 x RJ9 (4P4C) headset port

Other Physical Features

- › Color: Classic Grey
- › Wall mountable
- › External Yealink AC adapter: AC 100~240V input
- › Power consumption (PSU): 1.65-2.94W
- › Power consumption (PoE): 2.33-3.35W
- › Dimension (W*D*H*T): 212 x 186 x 146 x 42 mm
- › Operating humidity: 10~95%
- › Operating temperature: -10 to +45°C (+14 to 113°F)
- › Storage temperature: -30 to +70°C (-22 to +158°F)

Management

- › Configuration: browser/phone/auto-provision
- › Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- › Auto-provision with PnP
- › Zero-sp-touch, TR-069
- › Phone lock for personal privacy protection
- › Reset to factory, reboot
- › Package tracing export, system log

Network and Security

- › SIP v1 (RFC2543), v2 (RFC3261)
- › Call server redundancy supported
- › NAT traversal: STUN mode
- › Proxy mode and peer-to-peer SIP link mode
- › IP assignment: static/DHCP
- › HTTP/HTTPS web server
- › Time and date synchronization using SNTP
- › UDP/TCP/DNS-SRV (RFC 3263)
- › QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- › SRTP for voice
- › Transport Layer Security (TLS 1.3)
- › HTTPS certificate manager
- › AES encryption for configuration file (AES256)
- › Digest authentication
- › OpenVPN, IEEE802.1X, L2TP VPN
- › IPv6
- › LLDP/CDP/DHCP VLAN
- › ICE
- › WPA2/WPA3
- › Secure boot
- › GARP (Generic Attribute Registration Protocol)

Package Features

- › Package content:
 - Yealink SIP-T34W IP phone
 - Handset with handset cord
 - Ethernet Cable (optional)
 - Stand (not applicable to US wall plate Standard)
 - Quick Start Guide
 - Power Adapter
- › Qty/CTN: 10 PCS
- › N.W/CTN: 10.286 kg
- › G.W/CTN: 11.236 kg
- › Giftbox size: 238 x 210 x 103 mm
- › Carton Meas: 535 x 443 x 250 mm

Compliance



NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

Americas (U.S., Canada, Latin America)

NEC Corporation of America

For further information please contact:

My Tel Pros
(984) 201-2000
sales@mytelpros.com
www.mytelpros.com