







The FANVIL V64 is the ultimate desk phone for businesses seeking a seamless communication experience. Equipped with state-of-the-art features such as built-in Wi-Fi, Bluetooth connectivity, and a vibrant color LCD screen, the V64 is the perfect ally to simplify business communication needs.

Highlights

- 3.5" color LCD screen
- Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- Support 6-party local conference
- Built-in 2.4/5 GHz Wi-Fi and Bluetooth 4.2
- Dual Gigabit Ethernet ports
- Up to 21 DSS keys, every DSS key can be set as Line/BLF/Speed Dial Key, etc

FANVIL V64 BUSINESS PHONE PRODUCT SPECIFICATIONS

Generic:

- 12 SIP lines
- HD voice
- PoE enabled
- 3.5-inch (480x320) color screen
- Handset / hands-free / headset mode
- Intelligent DSS keys
- Desktop Stand / Wall-mounted (need additional parts)
- · Optional external power supply

Phone Features:

- · Local Phonebook (1000 entries)
- Remote Phonebook (XML/LDAP, 1000 entries)
- Call logs (In/out/missed, 1000 entries)
- · Block/Allow List Call Filter
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Bluetooth 4.2: Support Bluetooth headset/ Pairing mobile devices
- Built-in Wi-Fi
 - 2.4 GHz, 802.11 b/g/n
 - 5 GHz, 802.11 a/n/ac
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- 6-way Conference
- Hot Line
- Hotdesking

Audio:

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7 KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.729A/B
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) /Background Noise Estimation (BNE) / Noise Reduction (NR) /Automatic Gain Control (AGC)

- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)
- VQM voice quality monitoring

Network:

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static IP / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: OpenVPN/L2TP
- VLAN
- LLDP
- CDP
- QoS
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

Protocols:

- SIP 2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- CDP
- LLDP
- PPPoF
- 802.1x
- Open VPN
- SNTP
- FTP/TFTP
- Support Jabra wireless headset (Through Unite EHS20 EHS Cable)
- Support Recording (through server)
- · Action URL / Active URI
- uaCSTA
- SIP Hotspot
- Multicast
- Action Plan
- · Group listening

FANVIL V64 BUSINESS PHONE PRODUCT SPECIFICATIONS

Call Features:

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- · Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- BI F
- Call Parking/Pick-up
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- HTTP/HTTPS
- TR-069
- AES128 & AES256

Deployment & Management:

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP
- PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Import/Export
- Phonebook Import/Export
- Firmware

Physical Specifications:

- LCD: 3.5 inch (480x320) color screen
- Keypad: 39 keys, including
 - 8 DSS keys with LED indicator light
 - 6 Function keys (Contact, Hold, MWI, Mute, Headset, Redial)
 - 4 Soft-keys
 - 4 Navigation keys
 - 1 OK key
 - 1 Return key
- 12 Standard Phone Digit keys
- · 2 Volume Control keys, (Up/Down)
- 1 Hands-free key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5.E Ethernet Cable x1
- Desk Stand x1
- Status Indicator Light x1 (Red)
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- USB 2.0 Port x1: Standard A, Connect with Flash Driver & USB headset
- Security lock port x1
- Power: DC5V/2A or PoE
- Working Temperature: 0~45
- Working Humidity: 10~95%
- Installation:
 - Desktop Stand
- Wall-mounted (need additional parts)
- · Color: Gunmetal
- Device Dimensions: 204x202x31mm
- Gift Box Dimensions: 307x258x71 mm
- Outer CTN Dimensions: 5536x380x327 mm (10 PCS)





J.D. Power 2020 Certified Assisted Technical Program, developed in conjunction with TSIA. Based on successful completion of an audit and exceeding a customer satisfaction benchmark for assisted support operations. For more information, visit www.jdpower.com or www.tsia.com. Intermedia Unite, Securifync, VoIP Scout, AnyMeeting and HostPilot are either trademarks or registered trademarks of Intermedia.net, Inc. in the United States and/or other countries.



